



AMERICAN COATINGS

TH SERIES THINNERS

American Coatings TH Series Thinners are formulated for a multitude of purposes. These thinners vary drying times in coatings, are used for cleaning up equipment, and enhance brushing or rolling characteristics.

<u>PRODUCT</u>	<u>DESCRIPTION</u>	<u>USES</u>	<u>FLASH POINT °SETA</u>
TH 311	Acetone	Thinning for Low VOC Products	-4° F
TH 315	Ketone	Clean Up EX, EM, EP Series	48° F
TH 317	Ketone	PU Series	100° F
TH 319	Aromatic Ester Blend	PU, SU, AU Series	110° F
TH 400	Aliphatic Hydrocarbon	Slow Evaporation AK Heavy Duty Primers SAK Series	108° F
TH 550	Aromatic Hydrocarbon	Clean Up AK Series	65° F
TH 600	Aromatic Hydrocarbon	AK, SAK, EX 8330, EX 8335, AC, CR And SAC Series	80° F
TH 620	Aromatic Hydrocarbon	AK, SAK, EX 8330, EX 8335, AC, CR, And SAC Series	105° F
TH 629	Aromatic/Glycol Ether	Epoxy Wash, Oil Residue	80° F
TH 700	Aliphatic Hydrocarbon	AK Heavy Duty Primers	45° F
TH 701	Aliphatic Hydrocarbon	Cleaner	45° F
TH 760	Aromatic Ketone Alcohol Blend	EX, EXA, EM Series and TL Epoxy Phenolics	48° F
TH 790	Aromatic Ketone Blend	Clean Up	49° F
TH 850	Aromatic Blend	Lacquer Thinner Clean Up	35° F

TH SERIES

SAFETY INFORMATION

DANGER! EXTREMELY FLAMMABLE VAPORS MAY CAUSE FLASH FIRE. HARMFUL IF INHALED CAUSES IRRITATION

Keep away from heat, sparks, and flame. Use adequate ventilation. Do not breathe vapors or spray mist. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use. Avoid contact with eye, skin and clothing. Wash thoroughly after handling.

FIRST AID

In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If affected by inhalation of vapor or spray mist, remove to fresh air.. If swallowed, get medical attention.

Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

NOTICE

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

FOR INDUSTRIAL USE ONLY!

DISCLAIMER

It is stated and the recommendations and suggestions herein are based upon experiments and supplier information believed to be reliable. No guarantee is made of their accuracy, however, and American Chemical Society ASSUMES NO LIABILITY FOR PRODUCT FAILURE OTHER THAN TO SUPPLY REPLACEMENT MATERIAL FOR PRODUCTS SHOWN TO BE DEFECTIVE WHEN DELIVERED OR RETURNED UNDER THE PURCHASE PRICE. Except as stated, THERE ARE NO WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS OR OTHERWISE. AMERICAN CHEMICAL SOCIETY SHALL NOT BE LIABLE FOR SPECIAL, INCIDENTAL AND CONSEQUENTIAL DAMAGES. No statement contained herein shall be construed as an inducement to infringe existing patents or as an endorsement of specific manufacturers.
Revised 3.05.